

# HOTFOIL-EHS

**6-WAY "LOW-BOY" HEAT TREATING POWER CONSOLES**



**THE "LOW-BOY" STANDARD 6-WAY MODEL**

**(CAN ACCOMMODATE UP TO A 125KVA TRANSFORMER)**

**6W/LBPC-73FC/A/R (RAMP-TO-SET-POINT) or 6W/LBPC-73FC/A/FA (FULLY-AUTO)**



LOW-BOY 6-WAY BACK VIEW

6W/LBPC-73FC/A/R Part# 21115R

(RAMP-TO-SET-POINT)

The Hotfoil-EHS Ramp to set-point controller allows you to put in a ramp rate / hour and a soak temperature. The controller will go to the set-point and hold it there waiting further instruction from the Technician.

6W/LBPC-73FC/A/FA Part# 21115FA

(Fully Automatic)

The Hotfoil-EHS Fully automatic controller allows you to put in a ramp rate / hour and a soak temperature, duration of the soak and a ramp down rate. Followed by an "END" this does the whole stress automatically. It does not wait for the Technician.

### Standard Features Include:

- **73FC (STANDARD) UPTO A 125KVA Air Natural Transformer**
- Primary 3-Phase Input Tappings of 480/575V, 3ph, 60hz.
- Secondary 80 volts @ 73KVA.
- A Shunt Trip Facility In Association With Over Temperature Winding Protection
- 110 Volt Fused Auxiliary Supply For Instrumentation, 1KVA
- Contactorized Switching With LED Indicators For Each Of The 6 Channels
- Albright 250 Amp Contactors
- **Size & Weight: 39" high x 37" deep x 25" wide. 790#'s**
- Choice of either *Fully Automatic* controls or *RAMP* Controls
- Ammeter with 6-way switch for each zone
- Heavy Duty 6 inch casters, (two fixed, two swivel) for easy moving

**Or we will manufacture to your specifications**

**HOTFOIL-EHS, INC.**

**2960 East State Street Extension, Hamilton, NJ 08619**

**Phone: 609-588-0900 Fax: 609-588-8333**

**[www.HOTFOILEHS.com](http://www.HOTFOILEHS.com)**